



MOTOROLA
GP328 PLUS
GP338 PLUS

***MOTOROLA'S SMALLEST
PROFESSIONAL RADIO***

COMPACT VERSATILE EASY TO USE

***GP328 PLUS & GP338 PLUS
PROFESSIONAL PORTABLE RADIOS***

**COMMON FEATURES OF THE
MOTOROLA GP328 PLUS AND
GP338 PLUS RADIOS**

ADVANCED AUDIO TECHNOLOGY

Sound quality is critical for effective communications. The GP Plus Radio series is specially equipped with Motorola's voice compression and expansion technology called X-PAND™. The X-PAND™ feature enables crisper, clearer and stronger audio quality, allowing users to continue communicating even in noisy conditions. In addition, low-level expansion enables further improvements in audio quality by reducing unwanted background noise usually heard during pauses in conversation.

LED BATTERY GAUGE

The tri-colour LED battery gauge at the top of the radio alerts the users to recharge the battery should the battery level run low.

SWITCHABLE RF POWER LEVEL

By just pressing one button, users can switch to a low power when communicating within limited range coverage or switch to a high power level when further distance is required. High transmit power optimises range coverage while a low transmit power conserves battery consumption.

**REPEATER/TALKAROUND
ENABLE/DISABLE**

Users have the freedom to communicate through a repeater for wide area coverage, or bypass a repeater and talk directly to another radio if the coverage is within the range or when the repeater fails.

TIGHT/NORMAL SQUELCH

Users have the flexibility to protect their communication by selecting to a tight squelch to filter interference of unwanted weak signal; or switch to normal squelch to increase coverage.

LITHIUM ION BATTERY OPTION

Using the latest technology in battery chemistry, Motorola's GP Plus series offers a Lithium Ion battery option which provides high power at a lighter weight.

**PROGRAMMABLE CHANNEL
SPACING (12.5/20/25 kHz)**

The series allows programmable channel spacing of 12.5/20/25 kHz; offering flexibility and easy migration of channel spacing requirements when the need arises.



GP328 PLUS 4CH

4 CHANNEL

Provides users with 4 channels to organise different work groups to meet their different communication needs.

CHANNEL SCAN

Allows the user to monitor activities on different channels.

SIGNALLING FEATURES

The GP328 Plus 4 channel model offers the following MDC1200 signalling:

- PTT-ID (Encode)
- Radio Check (Decode)

EMERGENCY "PERSONAL SAFETY" SIREN

At the touch of a button the Emergency "Personal Safety" Siren can be a activated emitting an ear piercing alarm.

PL/DPL

Private Line and Digital Private Line enables multiple work groups to be allocated to a common channel.

TIME-OUT-TIMER

Will time out communication after a predetermined time, allowing channel access to more users.

BUSY CHANNEL LOCKOUT

In the event of a busy channel the radio will alert the user that another person is on the channel.



GP328 PLUS 16CH

Building upon the features of the GP328 Plus 4Ch, the GP328 Plus 16Ch has the following additional features:

16 CHANNELS

Provides users maximum of 16 channels to organise different work groups to meet their different communication needs.

TONE TAGGING

Allows 8 different ringing tones to be assigned to 8 specific users/talkgroups providing audio caller identification to these 8 groups.

EMERGENCY ALARM/SIREN AND EMERGENCY CALL

In addition to the easy-to-use, one touch emergency "Personal Safety" siren button which emits a piercing alarm, the GP328 Plus 16Ch has an Emergency Call function which when activated in the event of critical situations will send a 'pre-canned' alert back to a pre-determined radio or base.

ENHANCED SIGNALLING FEATURES

MDC1200:

- Call Alert (Decode)
- Voice Selective Call (Decode)
- Selective Radio Inhibit

Quick Call II

- Call Alert (Decode)
- Voice Selective Call (Decode)

Dual Tone Multiple Frequency

(DTMF) Signalling (Encode)



GP338 PLUS 128CH

Equipped with a alpha-numeric keypad and display the GP338 Plus offers enhanced functionality in addition to the features of the GP328 Plus series.

128 CHANNELS

Provides up to a maximum of 128 channels providing greater flexibility in organising different work groups.

14-CHARACTER ALPHA-NUMERIC DOT MATRIX DISPLAY

The 14 character alpha-numeric display allows immediate communication of vital information such as PTT ID, radio strength indicator and signal strength indicator. In addition, the user-friendly icons make the information easy to read and understand. The keypad and display illuminations also provide the visibility to operate your radio in the dark.

RECEIVED SIGNAL STRENGTH INDICATOR

An easy to read on screen display indicator notifies users of signal strength in their vicinity.

NAME & TONE TAGGING

The capability of assigning 8 different ringing tones and visual caller IDs to 8 specific users/talkgroups enhances audio and visual caller identification for these 8 groups.

BATTERY STRENGTH INDICATOR

Easy to read on-screen LCD display indicator alerts users on low battery strength.

MENU KEYS

The easy to navigate menu keys allow users to select relevant functionalities.

PTT-ID

Every time the PTT button is pressed, it enables the transmission of the caller ID.

STATUS/MESSAGES

This feature enables you to replace frequently used voice calls with status messages, saving you valuable communication time.

CALL ALERT

If your call to a radio has no response, the radio will emit an alert tone until the other party takes action.

everybody

ACCESSORIES

VOICE SELECTIVE CALL

The radio users receive a unique individual or group voice message with an alert to indicate that it is a selective call.


PRIORITY SCANNING

Allows activity on different channels to be monitored. Any incoming call will be automatically switched to another available channel so that the call can be received.



ENHANCE YOUR RADIO CAPABILITIES

There is a wide range of accessories available to suit your needs. Adding genuine Motorola headsets, microphones, batteries, charger or carrying cases can enhance your operational productivity. Motorola's accessories are built to high quality standards and are specially engineered to ensure maximum performance of your radio, no matter what business you are in.



*JMKN4123
Programming
Cable*



*JMMN4062
Earpiece
with
Mic/PTT*



*JMMN4064
Ear Mic
VOX/PTT
Interface
Module*



*JMMN4066
Light Weight
Headset with
Boom Mic*



*JMMN4067
Remote
Speaker Mic*



*JMNN4023/4024
Slim & Hicap
Li-Ion Batteries*



*JMZN4020
Radio Wrist
Strap*

*Not pictured:
Single Rapid Charger
HTN3006
Multi-Unit Rapid Charger
TNTN4031A*



ly's talking

COMPACT, LIGHT AND RUGGED

Compact and instant communication is important to many operations, as is the ability to be mobile and move freely without being weighed down by your communication tools.

Motorola's newest professional two-way radio packs a range of cutting edge innovations into one compact and lightweight radio designed to continue the Motorola heritage of offering the very best that portable radios can offer.

The Motorola GP328 Plus non-keypad and GP338 Plus keypad two-ways radios - the smallest in Motorola's Professional Series, are compact and light, fitting easily into the palm of your hand. But don't let the size fool you. Built to Motorola's renowned quality standards they are packed with advanced technology ensuring uncompromising radio performance.



*Motorola
GP328 Plus
non-keypad
and GP338 Plus
keypad two-way
radios – the
smallest in
Motorola's
Professional
Series, that are
compact and
light, fitting
easily into the
palm of your
hand.*

Whatever industry you are from the GP Plus Series provides a tough, compact and lightweight communications solution.

SECURITY:

From transporting money to overseeing major events or providing professional protection, the rugged palm-sized GP328 Plus & GP338 Plus are lightweight and discreet allowing the user to easily conceal their radio. The specialist range of Motorola Genuine Accessories, such as surveillance equipment, audio headsets, etc, further enhances your radios operation.

MANAGEMENT:

Maintain a professional image and gain the speed and efficiency of radio communication with the compact and light GP328 Plus and GP338 Plus radios: you are assured of clear, instant communication at the touch of a button.

HOSPITALITY:

From conducting floor-to floor security checks to addressing urgent conference room requests or delivering personal items, the compact and lightweight GP328 Plus and GP338 Plus radios allow you to serve your guests faster and with increased mobility.

BUILT TO MEET MILITARY SPECIFICATIONS

The GP Plus Series are commercial quality radios which has been tested to MIL810 (C,D and E) Military Specification Standards including temperature extremes, solar radiation, rain, humidity, salt fog, dust, vibration and shock. These tests were conducted subject to specific military procedures.

GP328 PLUS & GP338 PLUS SPECIFICATIONS

GENERAL SPECIFICATION	VHF/UHF	
* Frequency (MHz)	136 - 174 / 330 - 400 / 403 - 470 / 450 - 527	
Channel Capacity	GP328 Plus is available in 4 & 16 Channels	GP338 Plus is 128 Channels
Power Supply	Provided through rechargeable battery - 7.5V	
Dimensions (Radio footprint height excluding knobs)	Height x Width x Depth	
With Li-Ion (Slim) Battery:	101.5mm x 55.5mm x 30.5mm	
With Li-Ion (Hicap) Battery:	101.5mm x 55.5mm x 35.5mm	
Weight	GP328 Plus	GP338 Plus
With Li-Ion (Slim) Battery:	250g	250g
With Li-Ion (Hicap) Battery:	270g	270g
Average Battery Life @ 5/5/90 Cycle		
With Li-Ion (Slim) Battery:	10 hours @ Low Power	8 hours @ High Power
With Li-Ion (Hicap) Battery:	14 hours @ Low Power	11 hours @ High Power
Sealing	Withstands rain testing per MIL STD 810 C / D / E and IP54	
Shock and Vibration	Protection provided via impact resistant housing exceeding MIL STD 810 C / D / E and TIA/EIA603	
Dust and Humidity	Protection provided via environment resistant housing exceeding MIL STD 810-C/D/E and TIA/EIA 603	

TRANSMITTER SPECIFICATION	VHF/UHF	
* Frequency (MHz)	136-174 / 330-400 / 403-470 / 450-527	
Frequency Separation	Full bandsplit	
Channel Spacing	12.5 / 20 / 25kHz	
Freq Stability (-30°C to 60°C, +25°C Ref.)	2.5ppm	
Power Output	5W (VHF), 4W (UHF)	
Modulation Limiting	±2.5 @ 12.5kHz, ±4.0 @ 20kHz, ±5.0 @ 25kHz	
FM Hum & Noise	-40dB	
Conducted/Radiated Emission	-36dBm < 1GHz / -30dBm > 1GHz	
Modulation FCC Type	12.5kHz 11K0F3E, 25kHz 16K0F3E	
Audio Response (from 6 dB/octave pre-emphasis 300-3000Hz)	+1 to -3dB	
Audio Distortion	3% < 5% 1kHz 60% dev	

RECEIVER SPECIFICATION	VHF	UHF
* Frequency (MHz)	136-174 / 330-400 / 403-470 / 450-527	
Frequency Separation	Full bandsplit	
Sensitivity (12dB SINAD) EIA	.35mV	.25mV
Intermodulation (EIA)	-65dB	70dB
Adjacent Channel Selectivity	60dB @ 12.5kHz, 70dB @ 25kHz	
Spurious Rejection	70dB	
Rated Audio	500mW	
Audio Distortion	<5%	3%
Hum & Noise	-40dB	
Audio Response (300-3000Hz)	+1 to -3dB	
Conducted Spurious Emission	-57dBm < 1GHz, -47dBm > 1GHz, FCC Part 15	

Portable Military Standards 810, C D and E						
	810 C		810 D		810 E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temp	501.1	1, 2	501.2	1, 2	501.3	1, 2
Low Temp	502.1	1	502.2	1, 2	502.3	1, 2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	1, 2	506.2	1, 2	506.3	1, 2
Humidity	507.1	2	507.2	2, 3	507.3	2, 3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8, 10	514.3	1	514.4	1
Shock	516.2	1, 2, 5	516.3	1, 4	516.4	1, 4

* Availability subject to country law and regulations. Specifications subject to change without notice. All specifications shown are typical. Radios meet applicable regulatory requirements.



Visit us at www.motorola.com/cgiss/AP
 MOTOROLA, THE Stylized M Logo and GP328 Plus and GP338 Plus are registered in the U.S. Pat. & Tm. Office. All rights reserved. All other product or service names are the property of their respective owners.

© 2003 Motorola, Inc.

GP328/338Plus. 01.Aust. Aug-03.

For more information, please contact:

One-Year Warranty

Each Motorola radio is backed by a one-year warranty on radio parts and labour.



Accelerated Life Testing
 Motorola's Accelerated Life Testing simulates five years of hard use in real life, EIA RS-316B in Shock, Vibration, Dust, Humidity, IP54 for Sealing.



MIL-STD 810C, D and E
 Stamp of approval from the U.S. Military for use in rough environments.



ISO 9001 Standard
 Compliance with ISO 9001 Standard - an international quality system assurance on design, development, production, installation and servicing of a product.